

3 Phase Programmable AC Source

» Product specification sheet



Kindly follow our WeChat official account for more information



3 Phase Programmable AC Source

Contents

SPS300VAC1800W	01
SPS300VAC3000W	01
SPS300VAC4500W	01
SPS300VAC6000W	03
SPS300VAC9000W	03
SPS300VAC12000W	03
SPS300VAC15000W	03

Selection List:

Model	Voltage	Current	Power	Corresponding page
SPS300VAC1800W	150V/300V	1800W	1-Phase/3-Phase	P01
SPS300VAC3000W	150V/300V	3000W	1-Phase/3-Phase	P01
SPS300VAC4500W	150V/300V	4500W	1-Phase/3-Phase	P01
SPS300VAC6000W	150V/300V	6000W	1-Phase/3-Phase	P03
SPS300VAC9000W	150V/300V	9000W	1-Phase/3-Phase	P03
SPS300VAC12000W	150V/300V	12000W	1-Phase/3-Phase	P03
SPS300VAC15000W	150V/300V	15000W	1-Phase/3-Phase	P03

3 Phase Programmable AC Source

MODEL	SPS300VAC1800W		SPS300VAC3000W		SPS300VAC4500W	
INPUT						
Voltage	90~265VAC		100~265VAC		100~265VAC	
Frequency	47~63Hz					
Phase	3 Phase,4Wire+Groud/Y Connect					
Max. Current	30A		45A		57A	
Power Factor at 220VAC Input, Full Load	≥0.96 Active PFC		≥0.98 Active PFC		≥0.98 Active PFC	
Efficiency	>81% (Peak) >80% at 220VAC, 50Hz input/220VAC, 50Hz		>85.5% (Peak) >85% at 220VAC, 50Hz input/220VAC, 50Hz		>87.5% (Peak) >87% at 220VAC, 50Hz input/220VAC, 50Hz	
3-Phase Output Mode(Per Phase)						
AC Power(Total)	1800VA		3000VA		4500VA	
AC Power(Per Phase)	600VA		1000VA		1500VA	
Max. Current (r.m.s)	0~150V(L)	5.6A	9.2A		13.8A	
	0~300V(H)	2.8A	4.6A		6.9A	
Max. Current (Peak)	0~150V(L)	32.4A	55.2A		82.8A	
	0~300V(H)	16.2A	27.6A		41.4A	
1-Phase Output Mode						
AC Power(Total) ¹⁾	1800VA		3000VA		4500VA	
Max. Current (r.m.s)	0~150V(L)	16.8A	27.6A		41.4A	
	0~300V(H)	8.4A	13.8A		20.7A	
Max. Current (Peak)	0~150V(L)	97.2A	165.6A		248.4A	
	0~300V(H)	48.6A	82.8A		124.2A	
DC Power (Per Phase)	1800W		3000W		4500W	
Max. Current (Total)	L 11.88A		L 19.5A		L 29.28A	
	H 5.67A		H 9.9A		H 14.64A	
3-Phase Output Mode(Per Phase)						
Total Harmonic Distortion (THD)	<0.5% (Resistive Load) at 15.0~70.0Hz and output voltage within the 80~140VAC at Low Range or the 160~280VAC at High Range; <1% (Resistive Load) at 70.1~500Hz and output voltage within the 80~140VAC at Low Range or the 160~280VAC at High Range; <1% (Resistive Load) at 501~1000Hz and output voltage within the 100~140VACat Low Range or the 160~280VAC at High Rang;					
Crest Factor(CF)	≤ 6					
Load Regulation	±0.2%F.S. (Resistive Load) at 15~100Hz ±0.5%F.S. (Resistive Load) at >100Hz					
Line Regulation	± 0.1V					
Voltage(AC) (L-N)	Range	0~300VAC, 150V/300V/Auto Mode				
	Resolution	0.1V				
	Accuracy	0.2% of setting +0.4%F.S at Voltage>3V				
Phase Angle (Starting /Ending)	Range	0~359.9°				
	Resolution	0.1°				
	Accuracy	± 1° @45~65Hz				
Voltage(DC)	Range	0~424VDC				
	Resolution	0.1V				
	Accuracy	0.3% of setting +0.4%F.S at Voltage>3V				
	DC Power	600W	1000W		1500W	
	Max. Current	L 3.96A	L 6.5A		L 9.76A	
		H 1.89A	H 3.3A		H 4.88A	
Ripple&Noise (Peak)	L <700mVrms @Bandwidth 20Hz to 1MHz		H <1100mVrms @Bandwidth 20Hz to 1MHz			
Ripple&Noise (r.m.s)	<4000mVp-p @Bandwidth 20Hz to 1MHz					
Current OC Fold Mode	Resolution	0.01A				
	Accuracy	0.5% of setting +1.0%F.S.				
	Response Time	<1400ms				
Frequency	Range	15~1000Hz				
	Resolution	0.1Hz(15.0~99.9Hz), 1Hz(100~1000Hz)				
	Accuracy	0.03% of setting				
Programmable Output Impedance	Not Support					
Harmonic & Interharmonics Simulation	Not Support					
Power Meter Function(Per Phase)						
Voltage	Range	AC 0~300VAC				
		DC 0~424VDC				
	Resolution	0.1V				
Accuracy	0.2% of setting +0.4%F.S. (Peak: 0.6% of setting +1%F.S.)					

3 Phase Programmable AC Source

MODEL		SPS300VAC1800W	SPS300VAC3000W	SPS300VAC4500W
Frequency	Range	15~1000Hz		
	Resolution	0.1Hz(15.0~99.9Hz), 1Hz(100~1000Hz)		
	Accuracy	0.1% of setting		
Current ^[2] (r.m.s)	Range	H 0.15A~5.6A	0.3A~9.2A	H 0.3A~13.8A
		L 0.1A~3A	0.1A~3A	L 0.1A~3A
	Resolution	0.01A		
	Accuracy	0.4%+1.0%F.S.		
Current ^[2] (Peak)	Range	0A~32.4A	0A~55.2A	0A~82.8A
	Resolution	0.01A		
	Accuracy	0.4%+1.5%F.S.		
Power	Range	0~612W	0~1020W	0~1530W
	Resolution	0.1W		
	Accuracy	0.4% of setting +0.3%F.S. at PF>0.2, Voltage >5V		
Power Apparent(VA)	Range	0~612VA	0~1020VA	0~1530VA
	Resolution	0.1VA		
	Accuracy	Voltage*Irms, Calculated value		
Power Resistive (VAR)	Range	0~612VAR	0~1020VAR	0~1530VAR
	Resolution	0.1VAR		
	Accuracy	$\sqrt{(VA)^2 - (W)^2}$, Calculated value		
Power Factor (PF)	Range	0.00~1.00		
	Resolution	0.01		
	Accuracy	W/VA, Calculated value		
Harmonic	Range	Not Support		
EXTRA FUNCTION				
Slew Rate	Range	AC Voltage 0.001~1200.000V/ms and Disable		
		DC Voltage 0.001~1000.000V/ms and Disable		
		Frequency 0.001~1600.000Hz/ms and Disable		
Remote Sense	Range	5V(rms), Max. Total power less than rated power		
Calibration		Firmware-based calibration through the digital interface or front panel display		
Test Function		Not Support		
Graphic Display		4.3" Color touch LCD		
Operation Key Feature		Soft key, Numeric key, Rotary Knob, Support USB disk		
Rack mount Handles		Yes		
FAN		Temperature Control		
Protection Circuits		OCP, OVP, OPP, OTP, RCP, PRI_UVP, PRI_OVP, PRI_OTP, PRI_OCP, USB_OCP		
Interface		USB, RS485, RS232, LAN(Optional); GPIB(Optional)		
ENVIRONMENTAL				
Operating Temperature		0°C~40°C		
Storage Temperature		-40°C~85°C		
Altitude		2000m		
Relative Humidity		5%~95%, non-condensing		
Temperature Coefficient		100ppm/°C at Voltage, 300ppm/°C at Current, 100ppm/°C at Frequency		
MECHANICAL				
Dimensions(W*H*D)		540.0*481.0*640.0 mm		
Package Dimensions (W*H*D)		660.0*575.0*800.0 mm		
Unit Net Weight		88.7kg	88.7kg	88.7kg
Accessories Weight		0.4kg		
Gross Weight		108.7kg	108.7kg	108.7kg
REGULATORY COMPLIANCE				
CE Mark		Installation Overvltage Category II;Class II equipment;indoor use only.		

[1] In single phase mode, the current shall be reduced to 90% for the consideration of current sharing.

[2] The tolerance will change slightly in high frequency condition;

All specifications are subject to change without notice.

3 Phase Programmable AC Source

MODEL		SPS300VAC6000W	SPS300VAC9000W	SPS300VAC12000W	SPS300VAC15000W	
INPUT						
Voltage		190~265VAC				
Frequency		47~63Hz				
Phase		3 Phase,4Wire+Groud/Y Connect				
Max.Current		42A	60A	75A	90A	
Power Factor at 220VAC Input, Full Load		≥0.99 Active PFC	≥0.98 Active PFC	≥0.99 Active PFC	≥0.99 Active PFC	
Efficiency		>87% (Peak) >86% at 220VAC, 50Hz input/230VAC, 50Hz output, Full Load	>86% (Peak) >85% at 220VAC, 50Hz input/230VAC, 50Hz output, Full Load	>87% (Peak) >86% at 220VAC, 50Hz input/230VAC, 50Hz output, Full Load	>87% (Peak) >86% at 220VAC, 50Hz input/230VAC, 50Hz output, Full Load	
3-Phase Output Mode(Per Phase)						
AC Power(Total)		6000VA	9000VA	12000VA	15000VA	
AC Power(Per Phase)		2000VA	3000VA	4000VA	5000VA	
Max.Current (r.m.s)	0~150V(L)	16A	27.6A	32A	46A	
	0~300V(H)	8A	13.8A	16A	23A	
Max.Current (Peak)	0~150V(L)	80A	165.6A	160A	184A	
	0~300V(H)	40A	82.8A	80A	92A	
1-Phase Output Mode						
AC Power(Total) ^①		6000VA	9000VA	12000VA	15000VA	
Max.Current (r.m.s)	0~150V(L)	48A	82.8A	96A	138A	
	0~300V(H)	24A	41.4A	48A	69A	
Max.Current (Peak)	0~150V(L)	240A	496.8A	480A	552A	
	0~300V(H)	120A	248.4A	240A	276A	
DC Power (Per Phase)		6000W	9000W	12000W	15000W	
Max.Current (Total)	L	33.9A	58.8A	67.8A	97.8A	
	H	16.95A	29.4A	33.9A	48.9A	
3-Phase Output Mode(Per Phase)						
Total Harmonic Distortion (THD)		<0.5% (Resistive Load) at 15.0~70.0Hz and output voltage within the 80~140VAC at Low Range or the 160~280VAC at High Range; <1% (Resistive Load) at 70.1~500Hz and output voltage within the 80~140VAC at Low Range or the 160~280VAC at High Range; <1% (Resistive Load) at 501~1000Hz and output voltage within the 100~140VACat Low Range or the 160~280VAC at High Rang;				
Crest Factor(CF)		≤5	≤6	≤5	≤4	
Load Regulation		±0.2%F.S. (Resistive Load) at 15~100Hz ±0.5%F.S. (Resistive Load) at >100Hz				
Line Regulation		±0.1V				
Voltage(AC) (L-N)	Range	0~300VAC, 150V/300V/Auto Mode				
	Resolution	0.1V				
	Accuracy	0.2% of setting +0.4%F.S at Voltage>3V				
Phase Angle (Starting/Ending)	Range	0~359.9°				
	Resolution	0.1°				
	Accuracy	±1° @45~65Hz				
Voltage(DC)	Range	0~424VDC				
	Resolution	0.1V				
	Accuracy	0.3% of setting +0.4%F.S at Voltage>3V				
	DC Power	L	2000W	3000W	4000W	5000W
		H	11.3A	19.6A	22.6A	32.6A
	Max.Current	L	5.65A	9.8A	11.3A	16.3A
H						
Ripple&Noise (Peak)	L	<700mVrms @Bandwidth 20Hz to 1MHz		H <1100mVrms @Bandwidth 20Hz to 1MHz		
	r.m.s)	<4000mVp-p @Bandwidth 20Hz to 1MHz				
Current CC Fold Mode	Resolution	0.01A				
	Accuracy	2.0% of setting +1.0%F.S.				
	Response Time	<1400ms				
Frequency	Range	15~1000Hz				
	Resolution	0.1Hz(15.0~99.9Hz), 1Hz(100~1000Hz)				
	Accuracy	0.03% of setting				
Programmable Output Impedance		Not Support				
Harmonic & Interharmonics Simulation		Not Support				
Power Meter Function(Per Phase)						
Voltage	Range	AC 0~300VAC				
		DC 0~424VDC				
	Resolution	0.1V				
Accuracy		0.2% of setting +0.4%F.S. (Peak: 0.6% of setting +1%F.S.)				

3 Phase Programmable AC Source

MODEL		SPS300VAC6000W	SPS300VAC9000W	SPS300VAC12000W	SPS300VAC15000W
Frequency	Range	15~1000Hz			
	Resolution	0.1Hz(15.0~99.9Hz), 1Hz(100~1000Hz)			
	Accuracy	0.1% of setting			
Current ^[2] (r.m.s)	Range	H 0.15A~20A	H 0.3A~27.6A	H 0.3A~32A	H 0.3A~46A
		M -	M 0.2A~20A	M 0.2A~20A	M 0.2A~20A
		L 0.1A~5A	L 0.1A~5A	L 0.1A~5A	L 0.1A~5A
		mA 0.02A~1.5A	mA 0.02A~1.5A	mA 0.02A~1.5A	mA 0.02A~1.5A
	Resolution	0.01A			
Accuracy	0.4%+1.0%F.S.				
Current ^[2] (Peak)	Range	0A~81.5A	0A~168.6A	0A~163A	0A~188A
	Resolution	0.01A			
	Accuracy	0.4%+1.5%F.S.			
Power	Range	0~2040W	0~3060W	0~4080W	0~5100W
	Resolution	0.1W			
	Accuracy	0.4% of setting +0.3%F.S. at PF>0.2, Voltage >5V			
Power Apparent(VA)	Range	0~2040VA	0~3060VA	0~4080VA	0~5100VA
	Resolution	0.1VA			
	Accuracy	Voltage*I _{rms} , Calculated value			
Power Resistive (VAR)	Range	0~2040VAR	0~3060VAR	0~4080VAR	0~5100VAR
	Resolution	0.1VAR			
	Accuracy	$\sqrt{(VA)^2 - (W)^2}$, Calculated value			
Power Factor (PF)	Range	0.00~1.00			
	Resolution	0.01			
	Accuracy	W/VA, Calculated value			
Harmonic	Range	Not Support			
EXTRA FUNCTION					
Slew Rate	Range	AC Voltage 0.001~1200.000V/ms and Disable			
		DC Voltage 0.001~1000.000V/ms and Disable			
		Frequency 0.001~1600.000Hz/ms and Disable			
Remote Sense	Range	5V(rms), Max. Total power less than rated power			
Calibration	Firmware-based calibration through the digital interface or front panel display				
Test Function	Not Support				
Graphic Display	5.6" Color touch LCD				
Operation Key Feature	Soft key, Numeric key, Rotary Knob, Support USB disk				
Rack mount Handles	Yes				
FAN	Temperature Control				
Protection Circuits	OCP, OVP, OPP, OTP, RCP, PRI_UVP, PRI_OVP, PRI_OTP, PRI_OCP, USB_OCP				
Interface	USB, RS485, RS232, LAN(Standard); GPIB(Optional)				
ENVIRONMENTAL					
Operating Temperature	0°C~40°C				
Storage Temperature	-40°C~85°C				
Altitude	2000m				
Relative Humidity	5%~95%, non-condensing				
Temperature Coefficient	100ppm/°C at Voltage, 300ppm/°C at Current, 100ppm/°C at Frequency				
MECHANICAL					
Dimensions(W*H*D)	560.0*945.0*700.0 mm				
Package Dimensions (W*H*D)	680.0*1120.0*860.0 mm				
Unit Net Weight	134.0kg	157.0kg	157.0kg	157.0kg	
Accessories Weight	0.4kg				
Gross Weight	173.0kg	195.0kg	195.0kg	195.0kg	
REGULATORY COMPLIANCE					
CE Mark	Installation Overvoltage Category II; Class II equipment; indoor use only.				

[1] In single phase mode, the current shall be reduced to 90% for the consideration of current sharing.

[2] The tolerance will change slightly in high frequency condition;

All specifications are subject to change without notice.

APM Technologies (Dongguan) Co., Ltd

Add: #7, Link Information Industry Park, Shuilianshan Road,
Nancheng, Dongguan, Guangdong, China

Tel: +86 769-2202 8588 ext:2892 Fax: +86 769-2202 6771

E-mail: overseas@apmtech.cn Web: en.apmtech.cn

